




Franklin F4000 Series

Designed to maximize plant yield and quality, the F4000 utilizes its “**Blood Orange**” rich yellow-red leaning spectrum to deliver efficiency and reliability that punches well above its weight class.




DESIGNED FOR LARGE SCALE COMMERCIAL GROW HOUSES

SPECIFICATION	
Input Power	330W
Input Voltage	120 - 277 VAC
Voltage Range	100 - 305 VAC
Input Current	3.7A
Min Power Factor	>0.95%
THD	<20%
Operation Frequency	50/60Hz
Max Operation Temp (F°/C°)	0 - 104° F / -18 - 40° C
Dimming	Knob Switch Dimming or External 0-10V
Dimmer Mode	25%-50%-75%-100% Sectional Dimming
Color Temperature	3000K-5000K-660nm-730nm
B:G:R:FR	14:33:47:6
PPF (400-700) (μmol/s)	831.6
PPE (μmol/j)	2.52
PPF (400-800) (μmol/s)	882.5
PF Eff (μmol/j)	2.67
12in PPFD (μmol/s/m²)	1560
Power Cord	8ft
Lifetime	Q90: >54,000 hrs



DIMENSIONS



A	Length:	42.00 Inches
B	Width:	14.37 Inches
C	Height:	2.83 Inches
D	Weight:	15.2 lbs.

CERTIFIED




CONTACT US TODAY



Franklin F4000 Series


KEY FEATURES:

- Full spectrum with enhanced reds for full cycle growth
- Control each fixture with 0-10V on-board dimmer or an entire space with a controller



DESIGNED FOR LARGE SCALE COMMERCIAL GROW HOUSES

WHY THE F4000 SERIES



Easy Install Design

Designed for simple installation. Suspension cables offer 4 and 2-point mounting options as well as ratchet clips that provide an alternative mounting option.



Efficiency Focused Driver

Provides a powerful driver. That allows for heat management assistance, and remove need for additional install step.



Control Capabilities

Control each individual fixture with a 0-10V on-board dimmer or connect up to 50 LED fixtures with a controller.

ORDER CODE TABLE

F **4000** **41** **UNV** **S** **B** **5** **P**

MODEL	POWER	SIZE	VOLTAGE	MOUNTING	SPECTRUM	LIFE RATING	ACCESSORIES
F = Flagship Indoor Series	4000 = 330 Watts	41 = 42" by 14'	UNV = 120-277V	S = All Suspension HW include	B = Blood Orange	5 =Q90> 54,000	P = NEMA plug Adapter



www.fsllcd.com

All trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. Flourishing Co. Limited 2021.

CONTACT US TODAY



Email



Phone



Web